USB Condenser Microphone Omnidirectional for Conferences

Description

This table microphone by Delock is suitable for use in conferences.

Optimal recordings
The microphone has a circle pattern (omnidirectional) and therefore captures the acoustic signal ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

Touch mute button & status LED
The touch mute button quickly mutes the microphone. The LED is red when muted and green when recording.

Headphone output
The microphone has a 3.5 mm stereo jack output for connecting headphones or speakers.

Plug & Play
Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.



Specification

- Connectors:
  1 x USB 2.0 Type-A male
  1 x 3.5 mm 3 pin stereo jack female
- Directivity: omnidirectional
- Sensitivity: -16 dB +/- 3 dB
- Frequency range: 100 Hz - 10 kHz
- Sample rate: 16 Bit / 44.1 kHz
- Signal-to-noise ratio (SNR): ca. 65 dB
- Mute-Button
- Status LED
- Cable length: ca. 1.5 m
- Colour: black
- Dimensions (Ø x H): ca. 75 x 19 mm
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- User manual

Item no. 20672

EAN: 4043619206728

Country of origin: China

Package: Retail Box

© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

Images







© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

General	
Function:	Plug & Play
Supported operating system:	Chrome OS
	Linux Kernel 4.4 or above
	Mac OS 10.9 or above
	Windows 10 32-bit
	Windows 10 64-bit
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8 32-bit
	Windows 8 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
LED indicator:	1 x
Interface	
connector:	1 x USB 2.0 Type-A male
Technical characteristics	
Frequency range:	100 Hz - 10 kHz
Voltage:	USB bus powered
Sensibility:	-16 dB +/- 3 dB
Sample rate:	16 Bit / 44.1 kHz
Signal noise ratio (SNR):	ca. 65 dB
Directivity:	omnidirectional
Physical characteristics	
Cable length:	1.5 m
Diameter:	75 mm
Height:	19 mm
LED colour:	red
	green

© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.