Delock Externer Industrie Hub 7 x USB 3.0 Typ-A mit 15 kV ESD Schutz

Description

This solid industry capable USB hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by seven USB Type-A connectors, which supports the USB Battery Charging specification BC1.2. Thus, connected devices such as smartphones can be charged faster. If necessary, an optional power supply or an optional power cable can be connected to the power socket.



Specification

- Connectors:
  1 x USB 3.0 Type-B female >
  7 x USB 3.0 Type-A female - Battery Charging specification BC1.2
  1 x 9 – 40 V DC jack
  1 x 3 pin terminal power connector
- Chipset: VIA VL811+
- Data transfer rate up to:
  SuperSpeed USB 5 Gbps,
  Hi-Speed 480 Mbps,
  Full-Speed 12 Mbps,
  Low-Speed 1.5 Mbps
- 8 x LED indicator
- USB ports with screw jacks
- Robust metal housing
- Removable wallmount brackets
- Power supply: Bus-powered or Self-powered
- Flexible power supply with 9 V to 40 V
- Automatic detection of the input polarity of the power connectors
- ESD protection up to 15 kV for all ports
- Dimensions (LxWxH): ca. 158 x 80 x 32 mm
- Colour: black
- Plug & Play

Power supply specification

- 9 - 40 V
- Dimensions:
  inside: ø ca. 2.1 mm
  outside: ø ca. 5.5 mm
  length: ca. 9 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, ex Linux Kernel 3.16.x, ex Mac OS 10.9
- PC or laptop with a free USB Type-A port

Package content

- Hub USB
- 1 x cable USB A male to USB B male, length ca. 1 m
- 2 x wall mounting brackets
- 1 x mounting for 35 mm DIN rail

Item no. 63311

EAN: 4043619633111

Country of origin: China

Package: Retail Box



© 2018 by Delock . All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

- 1 x 3 pin terminal block
- User manual


Images











© 2018 by Delock . All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

General	
Function:	Battery Charging BC1.2
	Plug & Play
Mounting type:	DIN rail
	Screw mounting
Supported operating system:	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	ex Linux Kernel 3.16
	ex Mac OS 10.9
LED indicator:	8 x
Interface	
Connector 1:	1 x USB 3.0 Type-B female
Connector 2:	7 x USB 3.0 Type-A female - Battery Charging specification BC1.2
connector 3:	1 x 9 – 40 V DC jack
connector 4:	1 x 3 pin terminal power connector
Physical characteristics	
Length:	158 mm
Width:	80 mm
Height:	32 mm
Colour:	black

© 2018 by Delock . All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.