
LTE Antenna SMA plug 0.1 - 4.5 dBi omnidirectional with tilt joint black

Description

This GSM / UMTS / LTE antenna can be connected to a GSM / UMTS / LTE device with SMA interface, in order to send and receive signals.





Specification

- Connector: SMA plug
- Frequency range:
  791 - 894 MHz
  1920 - 2170 MHz
- Antenna gain:
  0.1 - 1.2 dBi @ 791 - 894 MHz
  3.0 - 4.5 dBi @ 1920 - 2170 MHz
- Impedance: 50 Ohm
- Polarisation: linear, vertical
- VSWR: 3.0
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS
- Colour: black
- Length:
  ca. 296.10 mm (with tilt joint)
  ca. 245.00 mm (without tilt joint)
- Diameter:
  ca. 24.00 mm (top)
  ca. 28.50 mm (max.)
  ca. 13.50 mm (SMA)

System requirements

- Device with a free SMA jack

Package content

- LTE antenna

Item no. 88436


EAN: 4043619884360


Country of origin: Taiwan, Republic of China


Package: Retail Box

Images









© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

General	
Suitable for indoor:	yes
Interface	
connector:	SMA plug
Technical characteristics	
Frequency range:	1920 - 2170 MHz
	791 - 894 MHz
Gain:	0.1 - 1.2 dBi @ 791 - 894 MHz
	3.0 - 4.5 dBi @ 1920 - 2170 MHz
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 55 °C
Polarisation:	linear vertical
VSWR:	3.0
Physical characteristics	
Housing material:	ABS
Diameter connector:	13.50 mm
Length with tilt joint:	296.10 mm
Length without tilt joint:	245.00 mm
Colour:	black

© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.