Delock Active Optical USB-C™ Video Cable 4K 60 Hz 5 m

Description

This cable by Delock is suitable for connecting a USB-C™ monitor with a resolution of up to 4K Ultra HD (3840 x 2160 @ 60 Hz) to a computer with USB-C™ interface and DisplayPort alternate mode support. This active optical cable is particularly thin and can transmit signals without loss over longer distances.



5 m

Note

This cable is only compatible with DisplayPort (DP alt mode) devices and it will not work with Thunderbolt™ devices.

Item no. 84090

EAN: 4043619840908

Country of origin: China

Package: Box

Specification

- Connectors:
  2 x USB Type-C™ male
- DisplayPort 1.2 specification
- Transmission of audio and video signals
- Supports DP Alt Mode
- Supports no USB data transfer and no USB charging
- Fibre optical cable with low signal degradation
- Not affected by electromagnetic interference
- Cable diameter: ca. 5.4 mm
- Contacts gold-plated
- Fixed signal direction
- Data transfer rate:
  DisplayPort 1.2 up to 21.6 Gb/s
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Supports HDR (High Dynamic Range)
- Supports HDCP 1.4 and 2.2
- Colour: black
- Length incl. connectors: ca. 5 m

© 2023 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

System requirements

- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode
- Monitor with a free USB Type-C™ (DP Alt Mode) interface

Package content

- USB-C™ video cable

© 2023 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Specification:	USB Type-C™

Interface

Connector 1:	1 x USB 5 Gbps USB Type-C™ male
Connector 2:	1 x USB 5 Gbps USB Type-C™ male

Technical characteristics

Data transfer rate:	21,6 Gb/s
Maximum screen resolution:	3840 x 2160 @ 60 Hz

Physical characteristics

Cable colour:	black
Cable diameter:	5.4 mm
Cable length incl. connector:	5 m
Smallest bending radius:	20 mm

© 2023 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.