USB Microphone with Gooseneck and Mute Button

Description

This USB microphone by Delock can be used for voice and vocal transmissions.

Optimal recordings
The microphone has a cardioid polar pattern (unidirectional) and captures the sound ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

Mute button & LED ring
With the mute button in the middle of the microphone, the microphone can be quickly muted. The LED ring signals operational status with a blue or red light.

Flexible gooseneck
With the gooseneck, the microphone can be bent in the preferred direction.

Plug & Play
Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.



Specification

- Connector: 1 x USB 2.0 Type-A male
- Directivity: unidirectional
- Sensitivity: -35 dB +/- 3 dB
- Frequency range: 70 Hz - 15 kHz
- Sample rate: 16 Bit / 48 kHz
- Mute-Button
- Gooseneck, length ca. 7 cm
- Status LED
- Dimensions (LxWxH): ca. 196 x 23 x 23 mm
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 3.3 or above
- Mac OS 10.9 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- User manual

Item no. 66499

EAN: 4043619664993

Country of origin: China

Package: Retail Box

© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

Images







© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

General	
Function:	Plug & Play
Specification:	USB 2.0
Supported operating system:	Chrome OS
	Linux Kernel 3.3 or above
	Mac OS 10.9 or above
	Windows 10 32-bit
	Windows 10 64-bit
	Windows 8 32-bit
	Windows 8 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
LED indicator:	1 x
Interface	
connector:	1 x USB 2.0 Type-A male
Technical characteristics	
Frequency range:	70 Hz - 15 kHz
Voltage:	USB bus powered
Sensibility:	-35 dB +/- 3 dB
Sample rate:	16 Bit / 48 kHz
Directivity:	uni-directional
Physical characteristics	
Length:	196 mm
Width:	23 mm
Height:	23 mm
LED colour:	red
	blue

© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.