USB Print Server



FPS-1032

H/W Version: 2

Product Overview

The LevelOne FPS-1032 print server is an ideal network printing solution for small offices, home offices, schools and other businesses that require printer sharing over the same network. This print server is equipped with a 10/100Mbps autosensing Ethernet port and a USB 2.0 port that connected to USB printer.

Multi OS and Network Printing Protocol Support

The FPS-1032 1-port USB print server supports Windows ME/NT/2000/XP/2003/Vista and Win7 operating systems as well as Mac OS 8.1 and higher, UNIX/Linux and Netware (Bindery/NDS). Network Protocol supported includes TCP/IP, IPX, NetBEUI, AppleTalk, LPR, RAW TCP and SMB over TCP/IP for flexible use with different network clients connected to the same office network. The FPS-1032 also includes Internet Printing Protocol (IPP) support and Windows Print Monitor Technology to monitor printing jobs received.

Easy Installation Wizard

The LevelOne FPS-1032 is easily configurable using a Web Browser or Windows based configuration program included with the CD-ROM. The print server is easily managed through a Web based user interface and the firmware is upgradeable through TFTP, the windows set-up program or the Web based user interface.



1. Power Port
2. LED Indicators
3. Reset Button
4. RJ-45 LAN Port
5. USB Port
6. Wall-Mountable

Key Features

- USB print server for network print sharing
- High-speed USB 2.0 interface
- Fast Ethernet network connectivity
- Easy set-up wizard included
- Web based user interface
- Support multiple operating systems
- Support multiple network printing protocols

Related Products



FPS-1031
Print Server with 1 Parallel Port



FPS-1033
Print Server with 2 USB and 1 Parallel Ports

Technical Specification

Device Specifications

Standards Compliance
IEEE 802.3, 802.3u Ethernet Standards

Network Interface
1x 10/100Mbps Auto-sensing RJ-45 port
1x USB 2.0 Auto-sensing port
DHCP Client

Operating System Support
Windows ME/NT/2000/XP/2003/ Vista/ 7
Mac OS 8.1 or higher
UNIX/Linux
NetWare (Bindery/NDS)

Network Print Protocol Support
TCP/IP, IPX, NetBEUI, AppleTalk, LPR, RAW TCP, SMB over TCP/IP,Internet Printing Protocol (IPP)

Software Upgradeable
Web interface
Windows-based Setup Program
TFTP

Device Management
Web-based user interface
Windows-based Setup Program
SNMP & HP Web JetAdmin Support

Physical Specifications

LEDs
Power/Status, Link, Activity

Power Supply
5V, 2A


Dimension
73.16mm (L) x 64.75mm (W) x 28.39mm (H)

Weight
58g

Operating Temperature and Humidity
Operating: 0°C ~ 50°C @ 0% ~ 70% (non-condensing)
Storage: -5°C ~ 65°C @ 0%~ 80% (non-condensing)

EMI Certifications
CE, FCC Class B

Product Diagram



Order Information

FPS-1032: USB Print Server

Package Content

FPS-1032
Power Adapter
Quick Installation Guide
CD Manual/QIG/Utility

All mentioned brand names are registered trademarks and property of their owners. Technical specifications are subject to change without notice.

© Copyright Digital Data Communications GmbH. All Rights Reserved.