Delock USB 2.0 Cable USB Type-C™ male to male PD 3.1 240 W E-Marker 1 m red metal

Description

This USB cable by Delock enables the connection between a device with a USB Type-C™ connector and a PC or a laptop equipped with a free USB Type-C™ port.

USB Power Delivery (USB PD 3.1) support up to 240 watt

Support for the Extended Power Range resp. USB Power Delivery 3.1 standard means that connected devices can be supplied with power, up to 240 W (48 V / 5 A) is possible.

Metal housing and strain relief

Thanks to the elegant metal housing and sturdy strain relief on both sides, the cable is optimally protected against damage in everyday use.



1 m

Item no. 80050

EAN: 4043619800506

Country of origin: China

Package: Zip poly bag

Specification

- Connectors:
  2 x USB Type-C™ 2.0 male
- Chipset: E-Marker
- Connector with metal housing
- Cable gauge:
  26 + 28 AWG data line
  22 AWG power line
- Cable diameter: ca. 5 mm
- Contacts gold-plated
- Connectors gold-plated
- Cable triple shielded
- Data transfer rate up to 480 Mbps
- USB Power Delivery (USB PD 3.1) support up to 240 watt (48 V / 5 A)
- Colour: black / red
- Length incl. connectors: ca. 1 m

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

Package content

- USB cable

Images



© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Specification:	USB 2.0

Interface

Connector 1:	1 x USB Type-C™ male
Connector 2:	1 x USB Type-C™ male

Technical characteristics

Chipset:	E-Marker
Data transfer rate:	480 Mbps
Maximum load:	240 W
Maximum current:	5 A
Voltage:	48 V

Physical characteristics

Connector finishing:	gold-plated
Pin finishing:	gold-plated
Conductor gauge:	26 AWG data line 28 AWG data line 22 AWG power line
Shielding:	triple
Length:	1 m
Colour:	black / red
Cable diameter:	5 mm

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.