Delock 3.5″ USB 3.2 Gen 1 Front Panel 1 x USB Type-C™ + 2 x USB Type-A + SD and Micro SD slot

Description

This front panel by Delock can be installed into a free 3.5″ bay of a computer. It has two USB 3.2 Gen 1 Type-A and one USB 3.2 Gen 1 Type-C port. It will be connected to the motherboard internally via a pin header male port.

Integrated Card Reader
In addition, the hub with integrated card reader expands the PC by an SD and a Micro SD slot.



Specification

- Connectors:
  external:
  1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) USB Type-C™ female
  2 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type-A female
  1 x SD slot
  1 x Micro SD slot
  internal:
  1 x 19 pin USB pin header female port on the cable
  1 x SATA 15 pin power connector
- Chipset: VIA VL817, Genesys Logic GL3224
- Data transfer rate up to:
  SuperSpeed 5 Gbps,
  Hi-Speed 480 Mbps,
  Full-Speed 12 Mbps,
  Low-Speed 1.5 Mbps
- The Card Reader supports following memory cards:
  1. Slot Secure Digital
  SD, SD3.0 UHS-I, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, MMC-I, MMC-II, MMC 4.0, Mini SD, Mini SDHC, MMCmobile, RS-MMC, RS-MMC 4.0
  2. Slot Micro Secure Digital
  MicroSD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro
- Cable data:
  1 x 19 pin USB pin header female cable, length ca. 54 cm (without connectors)
- 3.5″ metal frame
- Colour: black
- Hot Swap, Plug & Play

System requirements

- Linux Kernel 3.3 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free 3.5″ bay
- Motherboard with a free 19 pin USB pin header male
- Power supply with SATA 15 pin receptacle

Package content

- 3.5″ front panel
- USB pin header female cable
- Screws
- User manual

Item no. 64058

EAN: 4043619640584

Country of origin: China

Package: Retail Box

© 2022 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

Images









© 2022 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

General	
Form factor:	3.5"
Function:	Hot Swap
	Plug & Play
Supported operating system:	Linux Kernel 3.3 or above
	Windows 10 64-bit
	Windows 8.1 64-bit
Interface	
External:	1 x Micro SD slot
	1 x SD slot
	1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ female
	2 x SuperSpeed USB (USB 3.2 Gen 1) USB Typ-A Buchse
Internal:	1 x 19 pin USB 3.0 pin header female
	1 x SATA 15 pin power connector
Technical characteristics	
Data transfer rate:	USB 3.2 Gen 1 up to 5 Gbps
Physical characteristics	
Housing material:	metal
Length:	102 mm
Width:	95 mm
Height:	26 mm
Colour:	black

© 2022 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.