
Delock PCI Express x1 Card to 1 x RJ45 2.5 Gigabit LAN i225

Description

The PCI Express card by Delock offers **one network port** with a data transfer rate up to **2500 Mbps**.

NBASE-T for higher speed
Modern services and new technologies require higher bandwidths. **NBASE-T technology** enables speeds of 1 Gbps and 2.5 Gbps with conventional networking cables. The best possible transmission rate is set automatically.



Specification

- Connectors:
  external: 1 x 2.5 Gigabit LAN RJ45 jack
  internal: 1 x PCI Express x1, V2.1
- Chipset: Intel i225V
- Data transfer rate:
  Ethernet up to 10 Mbps
  Fast Ethernet up to 100 Mbps
  Gigabit Ethernet up to 1000 Mbps
  NBASE-T with up to 2.5 Gbps
  PCI Express x1 up to 4 Gbps
- Supports IEEE 802.3 / 802.3u / 802.3z / 802.3ab
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Supports Wake On LAN (WOL)
- Supports 9k Jumbo Frames
- Supports PXE
- LED indicator for link and activity

System requirements

- Linux Kernel 5.8 or above
- Windows 10-64
- PC with one free PCI Express slot

Package content

- PCI Express card
- Low profile bracket
- Driver CD
- User manual

Item no. 89598

EAN: 4043619895984

Country of origin: China

Package: Retail Box

Images







© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

General	
Supported operating system:	Windows 10 64-bit
LED indicator:	Link and activity
Interface	
External:	1 x Gigabit LAN RJ45 jack
Internal:	1 x PCI Express x1, V2.0
Technical characteristics	
Chipset:	Intel® i225V v3
Data transfer rate:	Ethernet up to 10 Mbps
	Fast Ethernet up to 100 Mbps
	Gigabit Ethernet up to 1 Gbps
	Gigabit Ethernet up to 2.5 Gbps
Physical characteristics	
Slot bracket:	low profile
	standard

© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.