
Delock Adapter USB 2.0 Type-A > 1 x Serial DB9 RS-232

Description

This USB Type-A to serial adapter by Delock provides an RS-232 port for meters, POS systems, printers, modems, IoT devices, etc.

LED indicator
Three LEDs indicate at the RS-232 port the current transmission and reception status as well as the USB power supply.

Easy installation
The **integrated driver software** makes the adapter quick and easy to install on the computer.



Specification

- Connectors:
  1 x USB 2.0 Type-A male
  1 x serial RS-232 DB9 male
- Chipset: Prolific 2503
- Data transfer rate up to 1 Mbps
- Parity: even, odd, none, mark, space
- Stop bit: 1, 1.5, 2
- Data bit: 5, 6, 7, 8
- FIFO: 512 byte
- LED colour: red, yellow, green
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Length incl. connectors (L): ca. 2 m

System requirements

- Chrome OS
- Linux Kernel 3.3 or above
- Mac OS 10.9.5 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB 2.0 to 1 x serial adapter
- User manual

Item no. 64073

EAN: 4043619640737

Country of origin: China


Package:



Images







© 2019 by Delock . All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

General	
Function:	Plug & Play
Specification:	RS-232 (EIA / TIA)
Supported operating system:	Chrome OS
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Linux Kernel 3.3 or above
	Mac OS 10.9.5 or above
Interface	
Output:	1 x serial RS-232 DB9 male
Input:	1 x USB 2.0 Type-A male
Technical characteristics	
Chipset:	Prolific PL2503
Data transfer rate:	up to 921.6 Kbps
FIFO:	512 byte
Data transmission:	asynchronous
	full duplex
UART:	USB to serial UART
Physical characteristics	
Cable diameter:	4.4 mm
Cable length incl. connector:	2 m
Pin finishing:	gold-plated
Screw type:	#4-40 UNC
Shielding:	double
Colour:	transparent

© 2019 by Delock . All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.