# Delock Adapter USB 2.0 Type-A to 1 x serial RS-232 DB9 4 m

## Description

This USB Type-A to serial adapter by Delock provides an RS-232 port for meters, POS systems, printers, modems, IoT devices etc.




## Specification

- Connectors:
  1 x USB 2.0 Type-A male >
  1 x serial RS-232 DB9 male with screws
- Chipset: FTDI FT232
- Data transfer rate up to 460,8 Kbps
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Parity: even, odd, none, mark, space
- Stop bits: 1, 2
- Databits: 7, 8
- Flow control: none, Xon / Xoff, RTS / CTS
- FIFO: 128 Byte - RX
- FIFO: 256 Byte - TX
- Cable length incl. connectors: ca. 4 m

## System requirements

- Linux Kernel 2.6 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

## Package content

- USB 2.0 to 1 x serial adapter
- Driver CD
- User manual

## Item no. 66323

EAN: 4043619663231

Country of origin: China


Package: • Retail Box




## Images







| | |
|---|---|
| **General** | |
| Function: | Plug & Play |
| Specification: | USB 1.1 |
| | USB 2.0 |
| Supported operating system: | Mac OS 10.9 or above |
| | Windows 7 32-bit |
| | Windows 7 64-bit |
| | Windows 8.1 32-bit |
| | Windows 8.1 64-bit |
| | Windows 10 32-bit |
| | Windows 10 64-bit |
| | Linux Kernel 2.6 or above |
| **Interface** | |
| Connector 1: | 1 x USB 2.0 Type-A male |
| Connector 2: | 1 x Serial RS-232 DB9 male |
| **Technical characteristics** | |
| Chipset: | FTDI 232R |
| Data transfer rate: | up to 460,8 Kbps |
| FIFO: | 128 byte |
| | 256 Byte |
| Data transmission: | asynchronous |
| | Bi-directional |
| UART: | USB to serial UART |
| **Physical characteristics** | |
| Cable type: | UL AWM 2725 80 °C 30V VW-1 |
| Cable colour: | black |
| Cable length: | 4 m |
| Pin finishing: | gold-plated |
| Shielding: | double |
| Colour: | grey / black |