Product datasheet

Specifications



APC Easy UPS, 700VA, Tower, 230V, 4x IEC C13 Outlets, AVR

BVX700LI

Overview

Lead Time	Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Main Output Voltage	230 V AC 1 phase
Rated Power In W	360 W
Rated Power In Va	700 VA
Input Connection Type	IEC 60320 C14
Output Connection Type	4 IEC 320 C13
Cable Length	1.22 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	User manual

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	8 h
Battery Voltage	12 V
Battery Capacity	7.0 Ah
Battery Life	2…3 year(s)
Replacement Battery	APCRBC110
Extended Runtime	0

General

Max Runtime	120 min
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ups Size	WS

Physical

Colour	Black
Height	13.8 cm
Width	9.8 cm
Depth	31 cm
Net Weight	4.2 kg
Mounting Support	Floor
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 5 Hz auto sensing
Input Voltage Limits	140...300 V 230 V AC
Cos Phi	0.51

Output

Maximum Configurable Power In W	360 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Full Load Runtime	00:00:01 360 W
Graph Display	1
Half Load Runtime	00:06:00 180 W
Maximum Configurable Power In Va	700 VA
Transfer Time	6 ms typical : 10 ms maximum

Conformance

Product Certifications	CE CB
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment Protection Policy	Lifetime : 50000 euros

Environmental

Ambient Air Temperature For Operation	0…40 °C
Relative Humidity	0…95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-15…40 °C

Storage Relative Humidity	0…95 % non-condensing
Storage Altitude	0…3000 m
Acoustic Level	40 dBA
Ip Degree Of Protection	IP20

Surge Protection and Filtering

Surge Energy Rate	273 J

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.8 cm
Package 1 Width	31 cm
Package 1 Length	13.8 cm
Package 1 Weight	4.2 kg
Scc14	10731304404481

Contractual warranty

Warranty	2 years repair or replace

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Learn more about Green Premium >



Transparency



RoHS/REACh

Well-being performance

Reach Free Of Svhc	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information