LTE Antenna TS-9 plug 90° 2 - 3 dBi fixed omnidirectional with magnetic base and connection cable RG-174 50 cm outdoor black

Description

This antenna by Delock allows the usage of different LTE bands indoors and outdoors. It is completely compatible to GSM, UMTS, LTE, ZigBee, DECT, Z-Wave, NB-IoT, WLAN, Bluetooth, ISM, DECT, TETRA and LoRa .



Specification

• Connector: 1 x TS-9 plug 90°
• Frequency range:
690 - 960 MHz
1710 - 2700 MHz
• GSM, UMTS, LTE, ZigBee, DECT, Z-Wave, NB-IoT, WLAN, Bluetooth, ISM, DECT, LoRa
• Antenna gain: 2 - 3 dBi
• Impedance: 50 Ohm
• Polarisation: linear, vertical
• VSWR: 2.0
• Operating temperature: -10 °C ~ 55 °C
• Colour: black
• Cable: coaxial
• Cable type: RG-174
• Cable colour: black
• Cable attenuation: 1.5 dB @ 1.5 GHz per meter
• Cable diameter: ca. 2.7 mm
• Cable length incl. connector: ca. 50 cm
• Dimensions (LxD): ca. 265 x 10 mm
• Diameter magnetic base: ca. 30.0 mm

System requirements

• Device with one free TS-9 port

Package content

• Antenna


Item no. 12480

EAN: 4043619124800

Country of origin: China

Package: Zip poly bag

Images



© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

Interface	
Connector 1:	1 x TS-9 plug
Technical characteristics	
Frequency range:	1710 - 2700 MHz
	690 - 960 MHz
Antenna gain:	2 - 3 dBi
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 55 °C
Polarisation:	linear vertical
VSWR:	2.0
Physical characteristics	
Antenna length incl. magnetic base:	23.60 cm
Diameter magnetical base:	3.0 cm
Height magnetical base:	2.8 cm
Cable category:	coaxial
Cable type:	RG-174
Cable attenuation:	1.5 dB @ 1.5 GHz per meter RG-174
Cable colour:	black
Cable length:	50 cm
Cable diameter:	2.7 mm

© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.