Delock USB Type-C™ Splitter (DP Alt Mode) to 1 x HDMI + 1 x DisplayPort MST with USB Type-C™ PD

Description

This splitter by Delock is suitable for the connection of**a DisplayPort monitor and an HDMI monitor** to a computer with **USB-C™** interface and DisplayPort alternate mode support. Two monitors can be operated simultaneously at the outputs.

Multi-Stream Transport (MST)
The product is a Multi-Stream Transport (MST) hub and supports the extended desktop configuration of DisplayPort. In Windows, the connected monitors are controlled individually, and can be combined into one large display.

USB Power Delivery (USB PD 3.0) support up to 100 watt
Supports the USB Power Delivery 3.0 standard, which allows connected devices to be powered with up to 100 W (20 V / 5 A).



Item no. 87867

EAN: 4043619878673

Country of origin: China

Package: Retail Box

Specification

- Connectors:
  Input:
  1 x USB Type-C™ male
  1 x USB Type-C™ female (power supply)
  Output:
  1 x HDMI-A female
  1 x DisplayPort female
- Chipset: VMM6210
- DisplayPort 1.4 specification
- Active converter, Single- / Multi-Stream Transport Hub (SST / MST)
- Supports Display Stream Compression 1.2 (DSC)
- Supports HDR
- Supports HDCP 1.4 and 2.2
- Maximum resolution (depending on the system and the connected hardware):
  DisplayPort 1.4 Multi-Stream Transport (MST):
  2 displays: up to 3840 x 2160 @ 60 Hz
  DisplayPort 1.2 Multi-Stream Transport (MST):

© 2023 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

2 displays: up to 3840 x 2160 @ 30 Hz
- Functions: Mirrored or Extended (Windows only)
- Transmission of audio and video signals
- USB bus powered
- Colour: black
- Cable length incl. connectors: ca. 15 cm
- Dimensions (LxWxH): ca. 51.0 x 51.0 x 16.5 mm

System requirements

- Windows 8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-C™ Splitter (DP Alt Mode)
- User manual

Images



© 2023 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Specification:	DisplayPort 1.4
Supported operating system:	Windows 10 32-bit Windows 10 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 11

Interface

Output:	1 x DisplayPort 20 pin female 1 x HDMI-A 19 pin female
Input:	1 x USB Type-C™ female (power supply) 1 x USB Type-C™ male

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz

Physical characteristics

Housing colour:	grey
Housing material:	Aluminium
Cable length incl. connector:	15 cm
Length:	51 mm
Width:	51 mm
Height:	16.5 mm

© 2023 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.