Delock USB Type-C™ Docking Station 4K - HDMI / VGA / USB 3.1 / SD / LAN / PD 3.0

Description



This docking station by Delock can be connected to a computer with a USB-C™ DP Alt Mode or Thunderbolt™ 3 port and provides a variety of interfaces. One monitor can be operated at the **HDMI or VGA** output. **Three built-in USB ports** allow the use of peripherals, and connections for gigabit network, as well as an **SD** / **micro SD card reader**, complete the features.

USB Power Delivery (USB PD 3.0) support up to 100 watt
The docking station has a **USB Type-C™ Power Delivery** port to connect the power supply of the laptop or tablet to charge it. In addition it also supplies the USB ports with power. The docking station can also be used without a power supply.

Small sturdy helper
Due to its small dimensions and its **sturdy housing**, this Delock docking station is particularly suitable for travelling. It can simply be packed into the bag together with the laptop or tablet and used as needed.

Item no. 87735

EAN: 4043619877355

Country of origin: China

Package: Retail Box

Specification

- Connectors:
  1 x USB Type-C™ male
  1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ female
  1 x USB 3.0 Type-A female
  1 x USB 3.0 Type-A female - Battery Charging specification BC1.2
  1 x SD / SDHC / SDXC slot
  1 x Micro SD / SDHC / SDXC slot
  1 x HDMI-A 19 pin female
  1 x VGA 15 pin female
  1 x Gigabit LAN 10/100/1000 Mbps RJ45 jack
  1 x USB Type-C™ female (power supply)
- Resolution:
  HDMI up to 3840 x 2160 @ 30 Hz

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

VGA up to 1920 x 1080 @ 60 Hz
(depending on the system and the connected hardware)

- Transmission of audio and video signals
- Input power: 1 x USB Type-C™ female max. 100 W
- Metal housing
- Cable length without connectors: ca. 15 cm
- Colour: grey
- Dimensions (LxWxH): ca. 110 x 59 x 12 mm

System requirements

- Chrome OS 70.0 or above
- Linux Kernel 4.6 or above
- Mac OS 10.14.2 or above
- Windows 8.1/8.1-64/10/10-64
- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free Thunderbolt™ 3 port

Package content

- USB-C™ docking station
- User manual

Images



© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Supported operating system:	Chrome OS 70.0 or above Linux Kernel 4.6 or above Mac OS 10.14.2 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

Output:	1 x RJ45 jack 1 x HDMI-A female 1 x VGA 15 pin female 1 x SD slot 1 x Micro SD Slot 1 x USB Type-C™ female (data transfer) 1 x USB Type-C™ female (power supply) 2 x USB 5 Gbps Type-A female
Input:	1 x USB Type-C™ male

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 30 Hz 2560 x 1440 @ 60 Hz 1920 x 1080 @ 60 Hz

Physical characteristics

Colour:	grey / black

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.