DATASHEET

Delock Active USB Type-C™ to HDMI Cable (DP Alt Mode) 4K 60 Hz 2 m

Description

This cable by Delock enables the connection of an HDMI monitor to a PC or laptop with USB-C™ or Thunderbolt™ 3 port, such as a MacBook or a Chromebook. The interface has to support the DisplayPort Alternate Mode.



Specification

- Connectors:
  1 x USB Type-C™ male >
  1 x HDMI-A male
- Signal direction: USB Type-C™ input > HDMI output
- Chipset: Parade PS176
- High Speed HDMI specification
- Cable gauge: 32 AWG
- Cable diameter: ca. 4.7 mm
- Contacts gold-plated
- Transmission of audio and video signals
- Resolution up to 3840 x 2160 @ 60 Hz
  (depending on the system and the connected hardware)
- Supports 3D displays (1080p @ 120 Hz)
- Supports HDCP 1.3
- Supports Eyefinity
- 2 x ferrite core
- Colour: black
- Length incl. connectors: ca. 2 m

System requirements

- Mac OS 10.12 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode
  or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-C™ to HDMI cable

Item no. 85970

EAN: 4043619859702

Country of origin: China

Package: • Zip poly bag

Images



General	
Specification:	High Speed HDMI
Interface	
Connector 1:	1 x USB Type-C™ male
Connector 2:	1 x HDMI-A male
Technical characteristics	
Chipset:	Parade PS176
Maximum screen resolution:	3840 x 2160 @ 60 Hz
Physical characteristics	
Ferrite core:	2 x
Pin finishing:	gold-plated
Conductor gauge:	32 AWG
Diameter:	4.7 mm
Length:	2 m
Colour:	black