Delock M.2 Docking Station for M.2 NVMe / SATA SSD with USB 10 Gbps USB Type-C™ male

Description

This M.2 docking station by Delock enables the installation of an**M.2 PCIe NVMe** SSD or **M.2 SATA** SSD and it can be connected via USB to the PC or laptop.



Item no. 64254

EAN: 4043619642540

Country of origin: China

Package: Retail Box

Combo docking station

The big advantage of this Delock M.2 docking station is that both SATA and PCIe (NVMe) M.2 SSDs can be inserted into the docking station. The memory is **automatically recognized by the chipset** and can then be used.

Ideal test equipment

The M.2 SSD is simply plugged into the slot and connected to the device via USB-C™ plug. Therefore, the docking station is most suitable as test equipment.

Specification

- Connectors:
  1 x USB 10 Gbps USB Type-C™ male
  1 x M.2 key M slot
- Chipset: Realtek RTL9210B
- Supports M.2 modules with key M or key B+M based on SATA or PCIe (NVMe)
- Supports NVM Express (NVMe)
- Bootable
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- 1 x On / Off switch
- Cable length without connectors: ca. 15 cm
- Dimensions: diameter ca. 60 mm, height ca. 19 mm
- Hot Plug, Plug & Play

System requirements

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- Android 11.0 or above
- Chrome OS
- Linux Kernel 5.15 or above
- Mac OS 12.4 or above
- Windows 10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 or Thunderbolt™ 4 port

Package content

- M.2 docking station
- User manual

Images





© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Function:	Plug & Play bootable
Supported operating system:	Chrome OS Windows 10 32-Bit Windows 10 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Mac OS 12.4 oder höher Android 11.0 or above Linux Kernel 5.15 or above
LED indicator:	power and activity

Interface

Connector 1:	1 x USB 10 Gbps Type-C™ male
Connector 2:	1 x M.2 key M slot

Technical characteristics

Chipset:	Realtek RTL9210B
Data transfer rate:	10 Gbps

Physical characteristics

Cable length:	15 cm
Colour:	black

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.