
GRAFIKKARTEN

GeForce RTX™ 4080 SUPER 16G SUPRIM X








SPECIFICATIONS

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES

TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.

TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.

Vapor Chamber

The GPU and memory modules are covered with a Vapor Chamber which rapidly transfers heat to Core Pipes.

Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.

Wave Curved 3.0

Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.

Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.

Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.

Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.

Generated 2024-01-18, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2024 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.© 2024 NVIDIA, the NVIDIA logo, GeForce, SHIELD, and NVIDIA G-SYNC are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries.