ICY DOCK®



Efficient Storage Solution (or Unleash PCIe Storage Potential)



Utilizing PCIe 4.0 Interface

Reduce cable clutter inside your system

PCIe 4.0 64Gbps — 10X FASTER

PCIe 3.0 32Gbps

SATA 6Gbps



Compatible with

Different length PCIe slots


Drive Swapping Made Simple



Removable Design

Add or remove U.2 / U.3 NVMe SSD in seconds

Large ventilation holes



Maximum Heat Dissipation

Side ventilated holes for optimal cooling

Key Features

- Supports 1 x U.2/U.3 NVMe SSD with a height of up to 9.5mm
- Compatible with PCIe 4.0 x4/ x8 /x16 Slot
- Supports PCIe Gen 4.0 x 4 speed up to 64Gbps
- Supports drive hot-plug without requiring the system to be powered down
- Active Power Technology (APT) – drive activity LED only powers up if there is a drive installed in the bay
- Optional 2-pin drive activity signal output - allows for easy transfer of the drive activity signal to the front of the computer case
- Connector is rated for a minimum of 10,000 insertion/removal cycles
- EMI Grounding – protects hard drives from electrical damage
- Narrow design allows for multiple bays to be installed side-by-side in a modular design
- Industry-leading 5-year limited warranty against all defects
- Complimentary support from professionally trained US-based technical support agents

Model Number	MB111VP-B
Color	Black
Support Drive Size	2.5" (up to 9.5mm height)
Compatible Drive Type	U.2/U.3
Drive Bay	1 x PCIe x4/8/16 Expansion Slot
Host Interface	PCIe 3.0/4.0 x8
Power Input	Via PCIe
Transfer Rate	Up to 64Gbps (Depending on drive Speed)
Support SSD Capacity	No Limitation
Structure / Material	Metal with partial ABS plastic
Drive Cooling	Metal heat dispersion with passive cooling
Product Dimension (L x W x H)	159.7 x 121 x 21.6mm
Product Net Weight	199.7g
Package Gross Weight	281.6g
Package Contents	Device, user manual, screws