

QHD Display
2.560 x 1.440

HDMI & DisplayPort
165 Hz

Adaptive-Sync
MPRT 1 ms

Blaulicht Reduzierung
HDR10

ERAZER
SPECTATOR X50 (MD21732)

Haupteigenschaften

68,6cm (27“) Widescreen LCD-Monitor mit LED-Backlight Technologie und einer QHD Auflösung von 2.560 x 1.440 Pixel

165 Hz – garantiert außerordentliche Bewegungsschärfe
Genießen Sie brillant scharfe Bilder bei schnellen Szenen

HDR10 (High Dynamic Range)
Dank des erhöhten Dynamikumfangs sehen Sie auch in dunklen Bereichen alles

Multifunktionaler Bildschirmfuß
Höhenverstellbar 150 mm
Neigungswinkle -5~20 Grad
Schwenkbar +/- 45°
Pivot 90°

HDMI® & DisplayPort® Eingang
Digitale HD-Bild- und Tonwiedergabe ohne Qualitätsverlust

2 integrierte Lautsprecher
2 x 3 Watt

Einfache Wandmontage dank VESA-Standard
Lochabstand 100 x 100 mm

Technische Daten

Display
LCD-Display mit ADS-IPS Technologie
Helligkeit 250 cd/m²
Statischer Kontrast 1.000:1
Dynamischer Kontrast 1.000.000:1
Physikalische Auflösung von 2.560 x 1.440 Pixel
Reaktionszeit 1 ms (MPRT typ.)
Reaktionszeit 8 ms (grey to grey typ.)
Blickwinkel (CR>10) 178° H/V (typ.)
Bildwiederholfrequenz 50-165 Hz
Energieeffizienzsklasse F

Anschlüsse
2 x HDMI® 2.0 mit HDCP 2.2 – Entschlüsselung
1 x DisplayPort® 1.2 mit HDCP 2.2 – Entschlüsselung
Kopfhöreranschluss
DC Netzschlussbuchse

Abmessungen (B x H x T) / Gewicht
Mit Fuß ca. 714 x 486-636 x 305 mm / 8,2 kg
Ohne Fuß ca. 714 x 421 x 60 mm / 6,4 kg
Karton ca. 937 x 533 x 173 mm / 11,1 kg

Lieferumfang
Full HD-Monitor, Bildschirmfuß, HDMI®-Kabel
externes Netzteil, Dokumentation



QHD Display
2.560 x 1.440

HDMI & DisplayPort
165 Hz

Adaptive-Sync
MPRT 1 ms

Blue light reduction
HDR10

ERAZER
SPECTATOR X50 (MD21732)

Main features

68.6cm (27“) widescreen LCD-monitor with LED-backlight technology and a QHD resolution of 2.560 x 1.440 pixel

165 Hz – guarantees extraordinary motion sharpness
Enjoy brilliantly sharp images in fast scenes

HDR10 (High Dynamic Range)
Thanks to the incredible dynamic range, you can see everything even in dark areas

Multifunctional screen base
Height adjustable 150 mm
Tilt angle -5~20 degrees
Swivel base +/- 45°
Pivot 90°

HDMI® & DisplayPort® input
Digital HD picture and sound reproduction without loss of quality

2 integrated speaker
2 x 3 watts

Easy wall mounting thanks to VESA-standard
Dimension 100 x 100 mm

Technical data

Display
LCD-display with ADS-IPS technology
Brightness 250 cd/m²
Static contrast 1.000:1
Dynamic contrast 1.000.000:1
Physical resolution of 2.560 x 1.440 pixel
Response time 1 ms (MPRT typ.)
Response time 8 ms (grey to grey typ.)
Viewing angle (CR>10) 178° H/V (typ.)
Refresh rate 50-165 Hz
Energy Efficiency Class F

Connectors
2 x HDMI® 2.0 with HDCP 2.2 – decryption
1 x DisplayPort® 1.2 with HDCP 2.2 – decryption
Headphone jack
DC input power jack

Dimensions (W x H x D) / weight
with stand app 714 x 486-636 x3 05 mm / 8.2 kg
without stand app 714 x 421 x 60 mm / 6.4 kg
Carton box app 937 x 533 x 173 mm / 11.1 kg

Scope of delivery
Full HD-monitor, Monitor stand base, HDMI®-cable, external power supply, Documentation