Diesel Einspritzreiniger 300 ml

Nichtentzündlicher, metallfreier Reiniger zum Lösen von Kohlenstoff- und Ascheablagerun-gen in Dieselpartikelfiltern. Die Applikation erfolgt über ein geeignetes Sprühsystem.

Leistung:
- Löst hervorragend Kohlenstoffablagerungen in Partikelfiltern
- Nicht entzündlich
- Reinigung ist ohne Demontage des Partikel-filters möglich
- Ausgezeichnete Materialvertäglichkeit
- Profi Anwendung mit Sprühpistole - hohe mechanische Reinigungswirkung

Einsatzbereich:
- Zur Wiederherstellung der vollen Aufnahme-kapazität des Dieselpartikelfilters
- Bei Leistungseinbußen oder Störungen durch verschmutzte Dieselpartikelfilter
- Zur Vorbeugung bei ungünstigem Fahrprofil

Anwendung:
- Temperatur- oder Drucksensor am Auspuff de-montieren.
- Applikation erfolgt über ein geeignetes Sprühsys-tem.
- Anschließend eine Probefahrt von mind. 20 Minu-ten durchführen.
- Nach der Reinigung mit dem Spülkonzentrat den Partikelfilter nachspülen.

Hinweis:
- Falls während der Probefahrt noch keine Rege-neration erfolgt ist, muss diese manuell über den Tester angeregt werden.



PCS004

GEFAHR

Gefahrenhinweise
H304 - Kann bei Verschlucken und Eindringen in die Atemwege tödlich sein. **H315** - Verursacht Hautreizungen. **H319** - Verursacht schwere Augenreizung. **H412** - Schädlich für Wasserorganismen, mit langfristiger Wirkung.

Sicherheitshinweise
P273 - Freisetzung in die Umwelt vermeiden. **P280** - Schutzhandschuhe tragen. **P301+P310** - BEI VERSCHLUCKEN: Sofort GIFTINFORMATIONSZENTRUM/Arzt anrufen. **P331** - KEIN Erbrechen herbeiführen. **P302+P352** - BEI BERÜHRUNG MIT DER HAUT: Mit viel Wasser waschen. **P332+P313** - Bei Hautreizung: Ärztlichen Rat einholen/ärztliche Hilfe hinzuziehen. **P305+P351+P338** - BEI KONTAKT MIT DEN AUGEN: Einige Minuten lang behutsam mit Wasser ausspülen. Eventuell vorhandene Kontaktlinsen nach Möglichkeit entfernen. Weiter ausspülen. **P337+P313** - Bei anhaltender Augenreizung: Ärztlichen Rat einholen/ärztliche Hilfe hinzuziehen.

Beinhaltet:
Kohlenwasserstoffe, C10-C13, n-Alkane, Isoalkane, Cyclene, < 2 % Aromaten Kohlenwasserstoffe, C10, Aromaten, <1 % Naphthalin

Kennzeichnung der Inhaltsstoffe gemäß Verordnung (EG) Nr. 648/2004
>= 30 % aliphatische Kohlenwasserstoffe, < 5 % aromatische Kohlenwasserstoffe.2



Diesel Injection Cleaner 300 ml

Cleaning agent for electronically and mechanically controlled injection nozzles. Ensures the injection system is clean and thus that combustion generates little soot and few particles.



PCS004

Performance:
- Cleans the injection system
- Ensures precise fine diesel fuel dosage
- Prevents knocking and rough idling
- Cuts smoke generation, especially under full load
- Full engine performance is regenerated

Application:
- Use in all adjustment work and emission metrology (soot particles)
- If soot generation is high
- For all repair work on diesel injection systems
- If engine performance drops

Directions:
- The cleaning process take place by the tank or filling the filter.
- Start the motor and run with different rotational speed; until the Diesel Injection Cleaner is depleted (max. 2000 U/min).
- One tin with 500 ml is suitable for engine capacity of 3 liters.

Cleaning process by tank:
- Optimally for the cleaning are tank contents of ca. 10 liters.
- Add the content of the tin to the tank.
- Take a test drive (If possible 30 km highway).

Cleaning process by filter:
- Renew the filter absolutely.
- Fill up the filter with the complete Diesel Injection Cleaner, then ventilate.
- Cleaning process ca. 10 min with changing rotational speed up to max. 2000 U/min.

DANGER

Danger warnings
H304 - May be fatal if swallowed and enters airways. **H315** - Causes skin irritation. **H319** - Causes serious eye irritation. **H412** - Harmful to aquatic life with long lasting effects.

Safety instructions
P273 - Avoid release to the environment. **P280** - Wear protective gloves. **P301+P310 -** IF SWALLOWED: Immediately call a POISON CENTER/doctor. **P331** - Do NOT induce vomiting. **P302+P352** - IF ON SKIN: Wash with plenty of water.
P332+P313 - If skin irritation occurs: Get medical advice/attention. **P305+P351+P338 -** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **P337+P313** - If eye irritation persists: Get medical advice/attention.

Contains: Hydrocarbons, C10 - C13, n-alkanes, iso-alkanes, cyclics, < 2 % aromates Kohlenwasserstoffe, C10, Aromaten, <1 % Naphthalin

Labelling for contents according to Regulation (EC) No 648/2004
>= 30 % aliphatic hydrocarbons, < 5 % aromatic hydrocarbons.

